

(Product Technical Data)

product model	100L	150L	200L	250L	300L
inner vessel diameter(mm)	Φ 365	Φ 365	Φ 480	Φ 480	Φ 480
water tank dimension(mm)	Φ 470	Φ 470	Φ 600	Φ 600	Φ 600
material and thickness of the inner vessel	SUS304-2B stainless steel/1.2mm	SUS304-2B stainless steel/1.2mm	SUS304-2B stainless steel/1.2mm	SUS304-2B stainless steel/1.2mm	SUS304-2B stainless steel/1.2mm
material and thickness of the shell	coloured steel/0.6mm	coloured steel/0.6mm	coloured steel/0.6mm	coloured steel/0.6mm	coloured steel/0.6mm
insulation thickness(mm)	52, 5	52, 5	60	60	60
Surface area heat exchanger top (m2)	----	0, 4	0, 4	0, 4	0, 4
Surface area heat exchanger bottom (m2)	0, 6	0, 6	0, 7	0, 7	0, 7
installation size of water pipe	brass 3/4"	brass 3/4"	brass 3/4"	brass 3/4"	brass 3/4"
rated heating power	2.5KW	2.5KW	2.5KW	2.5KW	2.5KW
Overall dimension(references) (mm)	Φ 470×1230	Φ 470×1620	Φ 600×1350	Φ 600×1600	Φ 600×1830
Packing case size(mm)	510×510×1290	510×510×1680	670×670×1410	670×670×1660	670×670×1890
Weight(references) (Kg)	32	43	50	55	72

