

TECH CONTROLLERS



2022 PRICE LIST

07.2022

EU

TABLE OF CONTENTS

Wireless system for wireless electric actuators control Via internet		4
Universal floor heating system with internet - 4 series		6
Wired floor heating system - 5 series		8
Wired floor heating system with internet - 7 series		10
Wireless floor heating system with internet - 8 series		11
Wired/ Wireless floor heating system with internet - 9 series		14
Wired floor heating system - 10 series		17
Internet room regulator for heating device		19
Wired room regulators two-state (on/off)		19
Wireless room regulators two-state (on/off)		20
Wired room regulators with RS communication		21
Wireless room regulators with RS communication		21
Room regulators for 55mm frame systems		22
Regulators for gas boilers		22
Air cleaning and sterilizing		22
Installation controllers		23
Solar installation controllers		24
Pump controllers		24
Charging boiler controllers		24
Boiler with feeder controllers		25
Fireplace controllers		25
Additional modules / accessories		26
Additional sensors		27
Fans		28

All prices are net value

In case of lack of casing colour selection color will be chosen randomly.

(Only for product with different colour variants)

Legend:

PRODUCT PHOTO	PRODUCT VERSION				
	PRODUCT DESCRIPTION AND NAME, FUNCTIONS				
	CATALOGUE NUMBER		EAN CODE	COLOUR	NET PRICE



EU-WiFi 8S WIFI MODULE FOR THERMOELECTRIC ACTUATORS

Functions: Control of up to 8 heating zones using:

- built-in temperature sensor
- 1 wired room temperature sensor EU-C-7p included
- possibility of connecting up to 8 system wireless sensors or wireless room regulators
- relay output NO/NC (to control the heating device, when heat needed)
- possibility of connecting up to 6 pcs of wireless electric actuators STT-868 or STT-869 for each zone

Maintain of the system via web app: www.emodul.eu

WG.20.0059

W_WIFI8S.01.EU01.1

5902479660998

217 €



EU-WiFi 8S p WIFI MODULE FOR THERMOELECTRIC ACTUATORS (FLUSH-MOUNTABLE)

Functions: Control of up to 8 heating zones using:

- possibility of connecting up to 8 system wireless sensors or wireless room regulators
- relay output NO/NC (to control the heating device, when heat needed)
- possibility of connecting up to 6 pcs of wireless electric actuators STT-868 or STT-869 for each zone
- 1 wireless temperature sensor EU-C-mini included

Maintain of the system via web app: www.emodul.eu

WG.20.0059

W_STR.8S.6.ME_W8S.01.EU01_K

5902479664194

217 €



EU-16S WiFi WIFI ROOM REGULATOR FOR CONTROL WIRELESS ELECTRIC ACTUATORS (FLUSH-MOUNTABLE)

Functions: Control of max 16 zones by means: built-in temperature sensor or by connecting additional 15 system wireless sensors or wireless room regulators. For each zone it is possible to connect up to 6pcs STT-868 or STT-869 wireless thermoelectric actuators. Each zone can have its own operation mode: constant temperature, temperature with time limitation or 6 different fully adjustable schedules. Room regulators displays: temperature, date, hour, alarm clock. Controller has display adjusting its brightness during the day. It is possible to update the room regulator via USB port. Easy installation in an electrical box(ø60mm). Power supply: 230V 50Hz, 4,3" colour touchscreen, **WiFi connection**,

Maintain of the system via web app: www.emodul.eu

WG.20.0038

W_16SWIFI.01.EU01.1

5902479661742

361 €

WG.20.0039

W_16SWIFI.01.EU02.1

5902479662244

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS



EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079

W_C8R.01.EU01.1

5902479661056

33 €

WG.03.0082

W_C8R.01.EU02.1

5902479662084



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WG.03.0085

W_CMINI.01.EU01.1

5902479662817

33 €



EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

W_CZU.CM.6_L.01.EU01

5902479661636

36 €



EU-C-8Zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

W_C8ZR.EU01.1

5902479661063

33 €



EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

W_R8B.01.EU01.1

5902479661070

44 €

WG.11.0192

W_R8B.01.EU02.1

5902479662091



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195

W_POK.R8.6.BP_BP.01.EU01

5902479663647

58 €

WG.11.0196

W_POK.R8.6.BP_BP.02.EU01

5902479663654



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644

W_POK.R8.6.SP_R8SP.01.EU01

5902479664385

88 €

W_POK.R8.6.SP_R8SP.02.EU01

5902479664378



EU-R-8pb PLUS BWIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR (FLUSCH MOUNTABLE)

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON!

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202	W_R8Z.01.EU01.1	5902479661087	56 €
WG.11.0203	W_R8Z.01.EU02.1	5902479662107	



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included).

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634	W_POK.F8.6_F8Z.01.EU01	5902479664408	78 €
	W_POK.F8.6_F8Z.02.EU01	5902479664415	



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR (FLUSCH MOUNTABLE)

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON!

ADDITIONAL MODULES AND ACTUATORS



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white	WG.03.0070	W_CZU.C2.6.N_A.01.EU01	5902479661339	39 €
RAL 7016 - antracite	WG.03.0069	W_CZU.C2.6.N_A.02.EU01	5902479664248	
RAL 8017 - brown	WG.03.0071	W_CZU.C2.6.N_A.03.EU01	5902479664255	
RAL 8003 - golden oak	WG.03.0068	W_CZU.C2.6.N_A.04.EU01	5902479664262	



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off. 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1	WG.05.0114	W_MW1.01.EU01.1	5902479661346	101 €
EU-MW-1-230V	WG.05.0116	W_MW1.02.EU02.1	5902479662374	



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

MWN-1	WG.05.0197	W_MWN1.01.EU01.1	5902479664507	101 €
MWN-1-230V	WG.05.0117	W_MWN1.02.EU02.1	5902479664392	



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140	W_MOD.RP4.6_A.01.EU01	5902479662824	101 €
------------	-----------------------	---------------	-------



STT-868 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. **Available thread M28x1,5 adapter**

WG.12.0005	W_868.01.EU01.1	5902479661124	73 €
------------	-----------------	---------------	------



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016	W_869.01.EU01.1	5902479662381	88 €
------------	-----------------	---------------	------

UNIVERSAL FLOOR HEATING SYSTEM WITH INTERNET - 4 SERIES



EU-L-4 WiFi WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

- Functions:**
- control of **4 voltage outputs** by 4 wired temperature sensors, or system wireless room regulators or wireless temperature sensors
 - voltage-free contact (for controlling additional heating device)
 - possibility of controlling the system via Internet (eModul app)**
 - possibility of control of **8 zones**:
 - 4 zones are controlled by system wireless temperature sensors or wireless room regulators
 - 4 zones with voltage outputs are controlled by 4 wired temperature sensors **EU-C-7p** or by systems wireless temperature sensors or wireless room regulators for each zone there is possibility of connecting 4 wireless electric actuators **STT-868**, or **STT-869**
 - possibility of connecting **4 wired floor NTC**- or **8 wireless - EU-C-8f**, floor sensors
 - possibility of connecting **8 wireless executive modules EU-MW-1 or EU-MW-1-230V**
 - software update via **USB**

WG.20.0044

W_L4.01.EU01.1

5902479662367

241 €

TEMPERATURE SENSORS - WIRED



EU-C-7p WIRED ROOM TEMPERATURE SENSOR

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0072

W_C7P.01.EU01.1

5902479661032

19 €

WG.03.0075

W_C7P.01.EU02.1

5902479662060

SYSTEM ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS



EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079

W_C8R.01.EU01.1

5902479661056

33 €

WG.03.0082

W_C8R.01.EU02.1

5902479662084



EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0076

W_C8F.01.EU01.1

5902479661643

36 €

WG.03.0078

W_C8F.01.EU02.1

5902479662220



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WG.03.0085

W_MINI.01.EU01.1

5902479661636

33 €



EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm

WG.03.0084

W_CZU.CM.6_L.01.EU01

5902479662817

36 €



EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries

WG.03.0083

W_C8ZR.EU01.1

5902479661063

33 €



EU-R-8b WIRELESS REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA batteries, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188

W_R8B.01.EU01.1

5902479661070

44 €

WG.11.0192

W_R8B.01.EU02.1

5902479662091



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195

W_POK.R8.6.BP_BP.01.EU01

5902479663647

58 €

WG.11.0196

W_POK.R8.6.BP_BP.02.EU01

5902479663654



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644

W_POK.R8.6.SP_R8SP.01.EU01

5902479664385

88 €

W_POK.R8.6.SP_R8SP.02.EU01

5902479664378



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON!

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, **power supply: 230V 50Hz to 5V included**

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

W_R8Z.01.EU01.1
W_R8Z.01.EU02.1

5902479661087
5902479662107

56 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included), **Equipment:** built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit.

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634

W_POK.F8.6_F8Z.01.EU01
W_POK.F8.6_F8Z.02.EU01

5902479664408
5902479664415

78 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON!

ADDITIONAL MODULES AND ACTUATORS



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white
RAL 7016 - antracite
RAL 8017 - brown
RAL 8003 - golden oak

WG.03.0070
WG.03.0069
WG.03.0071
WG.03.0068

W_CZU.C2.6.N_A.01.EU01
W_CZU.C2.6.N_A.02.EU01
W_CZU.C2.6.N_A.03.EU01
W_CZU.C2.6.N_A.04.EU01

5902479661339
5902479664248
5902479664255
5902479664262

39 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

W_MW1.01.EU01.1
W_MW1.02.EU02.1

5902479661346
5902479662374

101 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1-230V

WG.05.0197
WG.05.0117

W_MWN1.01.EU01.1
W_MWN1.02.EU02.1

5902479664507
5902479664392

101 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

W_RP3.01.EU01.1

5902479662824

101 €



STT-868 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. **Available thread M28x1,5 adapter**

WG.12.0005

W_868.01.EU01.1

5902479661124

73 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

W_869.01.EU01.1

5902479662381

88 €



STT-230/2 THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

T_000.00.000.00020
T_000.00.000.00021

5902479660691
5902479661490

29 €
29 €



STT-230/2 S THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Nut with M30 x 1,5 screw thread, Stroke: 3,7 mm., Class: IP50. Opening time: 3 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.000.00019

5902479661155

20 €



STT-230/2 T THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.203.00020

5902479663630

20 €



STT-230/2 M THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

NEW !

M30 x 1,5

T_000.00.000.00073

5902479665108

20 €

WIRED FLOOR HEATING SYSTEM - 5 SERIES



EU-L-5s WIRED CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

Functions: Possibility of control up to 50 thermostatic actuators via 8 room regulators:
 - 3 zones have 4 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),

WG.20.0134

W_L5S.01.EU01.1

5902479663784

93 €

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRED



EU-294 v1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0144

W_294V1.01.EU01.1

5902479661018

37 €

WG.11.0147

W_294V1.01.EU02.1

5902479662053



EU-T-2.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries,

NEW!

WG.11.0642

W_POK.294.2.6.P_PB.01.EU01

5902479665085

57 €



EU-295 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0151

W_295V3.01.EU01.1

5902479661544

50 €



EU-297 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0155

W_POK.297.6.P_PB.01.EU01

5902479662947

80 €

WG.11.0156

W_POK.297.6.P_PBN.01.EU01

5902479662954



EU-297z v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0158

W_POK.297.6.PZ_PZ.01.EU01

5902479663746

88 €

WG.11.0604

W_POK.297.6.PZ_PZN.01.EU01

5902479663753



EU-T-3.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0160

W_POK.297.6.P_PB.02.EU01

5902479663906

77 €

WG.11.0601

W_POK.297.6.P_PBN.02.EU01

5902479664217



EU-T-4.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

W_POK.290.6.V3_N.01.EU01

5902479664590

55 €



EU-292 v3 WIRED TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0137

W_292V3.01.EU01.1

5902479660257

73 €

WG.11.0139

W_292V3.01.EU02.1

5902479660264



EU-293 v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication,

Equipment: built-in room temperature sensor, front panel made of 1mm glass, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0142

W_POK.292.6.P_PB.01.EU01

5902479662886

92 €

WG.11.0143

W_POK.292.6.P_PBN.01.EU01

5902479662893



EU-293z v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.064	W_POK.292N.6.P_293N.PZ.EU01	5902479663791	109 €
	W_POK.292N.6.P_293N.PZ.EU02	5902479663807	



EU-F-2z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,

Equipment: built-in room temperature sensor, LCD display with no backlit, power supply: 230V,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0609	W_POK.F2.6_F2Z.01.EU01	5902479664095	66 €
WG.11.0636	W_POK.F2.6_F2Z.02.EU01	5902479664132	



EU-F-4z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlit, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass, 230V powered,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0633	W_POK.F4.6_A.01.EU01	5902479664118	92 €
	W_POK.F4.6_A.03.EU01	5902479664156	

ACCESORIES AND ACTUATORS



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm	P_002.02.00044.03.01	5902479661209	18 €
250cm	P_002.02.00045.03.01	5902479664279	19 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5	T_000.00.000.00020	5902479660691	29 €
M28 x 1,5	T_000.00.000.00021	5902479661490	29 €



STT-230/2 S THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Nut with M30 x 1,5 screw thread, Stroke: 3,7 mm., Class: IP50. Opening time: 3 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5	T_000.00.000.00019	5902479661155	20 €
-----------	--------------------	---------------	------



STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5	T_000.00.203.00020	5902479663630	20 €
-----------	--------------------	---------------	------



STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm, Max. operation temperature: 60°C. Power supply: 230V 50Hz

NEW !	M30 x 1,5	T_000.00.000.00073	5902479665108	20 €
--------------	-----------	--------------------	---------------	------



EU-293, EU-293z



EU-297, EU-297z



FRONT PANEL
MADE OF GLASS



FLOOR
SENSOR



HEATING/COOLING
FUNCTION



FLUSH MOUNTABLE
IN ELECTRICAL BOX

WIRED FLOOR HEATING SYSTEM WITH INTERNET - 7 SERIES

EU-L-7e WIRED CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

Functions: Possibility of control up to 50 thermostatic with 8 wired room temperature sensors EU-C-7p:
 - 3 zones have 4 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
 • one 230V output for pump
 • voltage-free contact (e.g. for controlling the heating device)
 • possibility of connecting EU-M7 control panel with RS communication
 • possibility of connecting EU-S05 Ethernet or EU-WiFi RS for controlling the installation via Internet
 • **possibility of connecting EU-i-1m mixing valve module or EU-i-1 mixing valve controller**
 • software update via USB
 • cooling and heating function



WG.20.0048	W_L7.02.EU01.2	5902479662688	212 €
------------	----------------	---------------	-------

TEMPERATURE SENSORS - WIRED

EU-C-7p WIRED ROOM TEMPERATURE SENSOR

Room temperature sensor

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0072	W_C7P.01.EU01.1	5902479661032	19 €
WG.03.0075	W_C7P.01.EU02.1	5902479662060	

ADDITIONAL MODULES AND ACTUATORS

EU-M-7n WIRED CONTROL PANEL FOR EU-L-7e CONTROLLER (FLUSH-MOUNTABLE)

Principle of operation: Controller is designed to control and preview the parameters of floor heating system.

Functions: Changing the parameters for each zone (schedule settings, set temperature), possibility of enabling/disabling particular zone, time/date settings, brightness settings, screensaver, alarm clock, screen lock, easy installation in an electrical box (ø60mm). Power supply: 230V 50Hz.



WG.11.0006	W_STR.M7.6.NJ_A.01.EU01	5902479663845	219 €
WG.11.0664	W_STR.M7.6.NJ_A.02.EU01	5902479664446	

EU-S05 INTERNET MODULE

Functions: remote control of the floor heating system, control of the set temperature in each zone, possibility of define the schedules, preview the temperatures history for each zone, possibility of personalization the main screen, alarms notifications via e-mail.

Equipment: power supply: 5V DC, T-connector for RS, RS communication cable for main controller.



WG.05.0025	W_S05.01.EU01.1	5902479660578	201 €
------------	-----------------	---------------	-------

EU-WiFi RS WIFI INTERNET MODULE (WIFI CONNECTION)

Functions: Same as in EU-S05. Internet connection via WiFi signal



WG.05.0040	W_WIFIRS.01.EU01.1	5902479660974	215 €
------------	--------------------	---------------	-------

EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Functions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.



WG.05.0030	W_I1M.01.EU01.1	5902479661612	123 €
------------	-----------------	---------------	-------

EU-513 INPUTS INTEGRATOR - 5

Functions: Integration of 5 voltage inputs, control of one 230V output



WG.05.0027	W_513.01.EU01.1	5902479661414	57 €
------------	-----------------	---------------	------

STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz



M30 x 1,5	T_000.00.000.00020	5902479660691	29 €
M28 x 1,5	T_000.00.000.00021	5902479661490	29 €

STT-230/2 S THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Nut with M30 x 1,5 screw thread, Stroke: 3,7 mm., Class: IP50. Opening time: 3 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz



M30 x 1,5	T_000.00.000.00019	5902479661155	20 €
-----------	--------------------	---------------	------

STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz



M30 x 1,5	T_000.00.203.00020	5902479663630	20 €
-----------	--------------------	---------------	------

STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz



NEW !	M30 x 1,5	T_000.00.000.00073	5902479665108	20 €
--------------	-----------	--------------------	---------------	------

WIRELESS FLOOR HEATING SYSTEM WITH INTERNET - 8 SERIES

Possibility of wireless control over thermostatic actuators

EU- L8e WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

Functions: Possibility of controlling up to 50 thermostatic actuators via 8 system room temperature sensors or room regulators

- 3 zones have 4 outputs each (in case of greater amount of actuators max load is 0,3 A),
- 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
- one 230V output for pump
- voltage-free contact (e.g. for controlling the heating device)
- possibility of connecting EU-M8e control panel with RS communication
- possibility of connecting EU-505 Ethernet or EU-WiFi RS for controlling the installation via Internet
- **possibility of connecting EU-i-1m mixing valve module or EU-I-1 mixing valve controller**
- software update via USB
- cooling and heating function
- possibility of connecting 3 additional KTY sensors or outdoor sensor (1 input replace 1 sensor or 1 room regulator)



WG.20.0050

W_L8E.01.EU01.1

5902479662640

270 €

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0079

W_C8R.01.EU01.1

5902479661056

33 €

WG.03.0082

W_C8R.01.EU02.1

5902479662084

EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.03.0076

W_C8F.01.EU01.1

5902479661643

36 €

WG.03.0078

W_C8F.01.EU02.1

5902479662220

EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm



WG.03.0085

W_CMNI.01.EU01.1

5902479661636

33 €

EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm



WG.03.0084

W_CZU.CM.6_L.01.EU01

5902479661636

36 €

EU-C-8zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries



WG.03.0083

W_C8ZR.EU01.1

5902479661063

33 €

EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0188

W_R8B.01.EU01.1

5902479661070

44 €

WG.11.0192

W_R8B.01.EU02.1

5902479662091

EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0195

W_POK.R8.6.BP_BP.01.EU01

5902479663647

58 €

WG.11.0196

W_POK.R8.6.BP_BP.02.EU01

5902479663654

EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0644

W_POK.R8.6.SP_R8SP.01.EU01

5902479664385

88 €

W_POK.R8.6.SP_R8SP.02.EU01

5902479664378

EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.



AVAILABLE SOON



TECH
CONTROLLERS

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, **power supply: 230V 50Hz to 5V included**

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202
WG.11.0203

W_R8Z.01.EU01.1
W_R8Z.01.EU02.1

5902479661087
5902479662107

56 €



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included).

Equipment: built-in room temperature and humidity sensor, LCD display, no backlit, 230V powered, Flush mountable in electrical box (ø60mm), no backlit.

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634

W_POK.F8.6_F8Z.01.EU01
W_POK.F8.6_F8Z.02.EU01

5902479664408
5902479664415

78 €



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlit, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON

ADDITIONAL MODULES AND ACTUATORS



EU-M-8n WIRELESS CONTROL PANEL FOR EU-L-8e CONTROLLER (FLUSH-MOUNTABLE)

Principle of operation: Controller is designed to control and preview the parameters of floor heating system.

Functions: Changing the parameters for each zone (schedule settings, set temperature), possibility of enabling/disabling particular zone, time/date settings, brightness settings, screensaver, alarm clock, screen lock, easy installation in an electrical box(ø60mm). Power supply: 230V 50Hz.

ONLY FOR EU-L-8e controller!

WG.11.0168
WG.20.0139

W_STR.M8.6.NJ_A.01.EU01
W_STR.M8.6.NJ_A.02.EU01

5902479663883
5902479664453

260 €



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

RAL 9010 - white
RAL 7016 - antracite
RAL 8017 - brown
RAL 8003 - golden oak

WG.03.0070
WG.03.0069
WG.03.0071
WG.03.0068

W_CZU.C2.6.N_A.01.EU01
W_CZU.C2.6.N_A.02.EU01
W_CZU.C2.6.N_A.03.EU01
W_CZU.C2.6.N_A.04.EU01

5902479661339
5902479664248
5902479664255
5902479664262

39 €



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm
250cm

P_002.02.00044.03.01
P_002.02.00045.03.01

5902479661209
5902479664279

18 €
19 €



EU-WiFi RS WIFI INTERNET MODULE (WIFI CONNECTION)

Functions: Same as in EU-505. Internet connection via WiFi signal

WG.05.0040

W_WIFIRS.01.EU01.1

5902479660974

215 €



EU-505 INTERNET MODULE

Functions: remote control of the floor heating system, control of the set temperature in each zone, possibility of define the schedules, preview the temperatures history for each zone, possibility of personalization the main screen, alarms notifications via e-mail.

Equipment: power supply: 5V DC, T-connector for RS, RS communication cable for main controller.

WG.05.0025

W_505.01.EU01.1

5902479660578

201 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Fuctions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030

W_I1M.01.EU01.1

5902479661612

123 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114
WG.05.0116

W_MW1.01.EU01.1
W_MW1.02.EU02.1

5902479661346
5902479662374

101 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1 230V

WG.05.0197
WG.05.0117

W_MWN1.01.EU01.1
W_MWN1.02.EU02.1

5902479664507
5902479664392

101 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

W_MOD.RP4.6_A.01.EU01

5902479662824

101 €



EU-513 INPUTS INTEGRATOR - 5

Functions: Integration of 5 voltage inputs, control of one 230V output

WG.05.0027

W_513.01.EU01.1

5902479661414

57 €



STT-868 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. **Available thread M28x1,5 adapter**

WG.12.0005

W_868.01.EU01.1

5902479661124

73 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

W_869.01.EU01.1

5902479662381

88 €



STT-230/2 THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5
M28 x 1,5

T_000.00.000.00020
T_000.00.000.00021

5902479660691
5902479661490

29 €
29 €



STT-230/2 S THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Nut with M30 x1,5 screw thread, Stroke: 3,7 mm., Class: IP50. Opening time: 3 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.000.00019

5902479661155

20 €



STT-230/2 T THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.203.00020

5902479663630

20 €



STT-230/2 M THERMOELECTRIC ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

NEW !

M30 x 1,5

T_000.00.000.00073

5902479665108

20 €



**WIRELESS
ROOM REGULATOR
FOR 55mm
FRAME SYSTEMS
EU-F-8z**

EU-L-9r WIRED/WIRELESS CONTROLLER FOR THERMOSTATIC ACTUATORS (8 SECTIONS)

Functions: - possibility of control up to **50** thermostatic actuators by **19** outputs:
 - 3 zones have 3 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 5 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - one 230V output for pump
 - voltage-free contact (e.g. for controlling the heating device)
 - possibility of connecting EU-i-1m mixing valve module or EU-i-1 mixing valve controller
 - possibility of connecting up to **4 controllers in series (up to 32 zones)** and managing system via 1 control panel
 - possibility of controlling the system via Internet (eModul app)
heating/cooling mode
 - 4-wire cord for communication with peripheral devices
 - possibility of connecting system wireless room temperature sensors, room regulators or electric actuators
software update via USB



WG.20.0056	W_STR.L9.6.RJ_R.01.EU01	5902479662831	337 €
------------	-------------------------	---------------	-------

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED

EU-R-9b DEDICATED WIRED ROOM REGULATOR FOR EU-L-9r CONTROLLER

Functions: room temperature control, additional control based on floor temperature (if floor sensor is used), wired communication **4-wire / no batteries**
Equipment: built-in room temperature sensor, LCD display, no backlight



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0205	W_R9B.01.EU01.1	5902479662275	41 €
WG.11.0208	W_R9B.01.EU02.1	5902479662329	

EU-R-9s PLUS DEDICATED WIRED ROOM REGULATOR FOR EU-L-9r CONTROLLER

Functions: room temperature control, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight, communication **4-wire / no batteries**



Equipment: built-in room temperature and humidity sensor, LCD display,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0211	W_POK.297.6.RS_R9SP.01.EU01	5902479663852	65 €
WG.11.0107	W_POK.297.6.RS_R9SP.02.EU01	5902479664170	

TEMPERATURE SENSORS - WIRED

EU-C-7p WIRED ROOM TEMPERATURE SENSOR

Room temperature sensor



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0072	W_C7P.01.EU01.1	5902479661032	19 €
WG.03.0075	W_C7P.01.EU02.1	5902479662060	

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRELESS

EU-C-8r WIRELESS ROOM TEMPERATURE SENSOR

Power: 2xAAA batteries



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0079	W_C8R.01.EU01.1	5902479661056	33 €
WG.03.0082	W_C8R.01.EU02.1	5902479662084	

EU-C-8f WIRELESS FLOOR TEMPERATURE SENSOR

Floor temperature sensor NTC type, power supply: 2x AAA batteries



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.03.0076	W_C8F.01.EU01.1	5902479661643	36 €
WG.03.0078	W_C8F.01.EU02.1	5902479662220	

EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm



WG.03.0085	W_CMINI.01.EU01.1	5902479661636	33 €
------------	-------------------	---------------	------

EU-CL-mini WIRELESS ROOM TEMPERATURE SENSOR IN HERMETIC CASING

MEETS THE IP64 STANDARD

Dimensions: 44,3mm x 44,3mm x 17mm



WG.03.0084	W_CZU.CM.6_L.01.EU01	5902479661636	36 €
------------	----------------------	---------------	------

EU-C-8Zr WIRELESS OUTSIDE TEMPERATURE SENSOR

Power: 2xAAA batteries



WG.03.0083	W_C8ZR.EU01.1	5902479661063	33 €
------------	---------------	---------------	------

EU-R-8b WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlight



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0188	W_R8B.01.EU01.1	5902479661070	44 €
WG.11.0192	W_R8B.01.EU02.1	5902479662091	



EU-R-8b PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, temperature control on the basis of floor temperature (in case of using NTC floor sensor - not included), LCD display, 2xAAA Batteries, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0195	W_POK.R8.6.BP_BP.01.EU01	5902479663647	58 €
WG.11.0196	W_POK.R8.6.BP_BP.02.EU01	5902479663654	



EU-R-8s PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0644	W_POK.R8.6.SP_R8SP.01.EU01	5902479664385	88 €
	W_POK.R8.6.SP_R8SP.02.EU01	5902479664378	



EU-R-8pb PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, powered 2xAAA batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON

ROOM REGULATORS - 230V, WIRELESS



EU-R-8z WIRELESS ROOM REGULATOR

Functions: room temperature control, heating program with time limit. Built-in room temperature sensor, LED display, power supply: 230V 50Hz to 5V included

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0202	W_R8Z.01.EU01.1	5902479661087	56 €
WG.11.0203	W_R8Z.01.EU02.1	5902479662107	



EU-F-8z WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, heating program with time limit, additional control based on floor temperature (in case of using NTC floor sensor - not included),

Equipment: built-in room temperature and humidity sensor, LCD display, no backlight, 230V powered, Flush mountable in electrical box (ø60mm), no backlight,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0634	W_POK.F8.6_F8Z.01.EU01	5902479664408	78 €
	W_POK.F8.6_F8Z.02.EU01	5902479664415	



EU-R-8pz PLUS WIRELESS ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, heating program with time limit. Built-in room temperature and humidity sensor, additional control based on floor temperature (in case of using NTC floor sensor - not included), LCD display with temporary backlight, powered 230V, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

AVAILABLE SOON

ADDITIONAL MODULES AND ACTUATORS



EU-M-9r WIRED CONTROL PANEL + WIFI MODULE (FLUSH MOUNTABLE)

Functions: Zone registration, changing parameters for each zone (schedules, set temperature), possibility of activate/deactivate zone, date/hour settings for whole system, screensaver, screen lock. **NO TEMPERATURE SENSOR BUILT IN CONTROLLER., WiFi communication (system management via eModul app),** Flush mountable in electrical box (ø60mm). Power supply 230V 50Hz, wired communication 4-cable cord / no batteries

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0175	W_STR.M9.6.RJ_R.01.EU01	5902479662428	398 €
WG.11.0178	W_STR.M9.6.RJ_R.02.EU01	5902479662855	



EU-M-9t WIRED CONTROL PANEL + WIFI MODULE

Functions: Zone registration, changing parameters for each zone (schedules, set temperature), possibility of activate/deactivate zone, date/hour settings for whole system, screensaver, screen lock. **NO TEMPERATURE SENSOR BUILT IN CONTROLLER., WiFi communication (system management via eModul app),** wired communication 4-cable cord / no batteries, RS power adapter in set,

WG.11.0252	W_STR.M9.6.RJ_R.03.EU01	5902479664019	398 €
WG.11.0586	W_STR.M9.6.RJ_R.04.EU01	5902479664439	



EU-C-2N WINDOW SENSOR

Functions: wireless communication, window opening signal, heating control, compact in size, long-life battery, discreet design.

Power: EVE ER14250 S battery

WG.03.0070	RAL 9010 - white	W_CZU.C2.6.N_A.01.EU01	5902479661339	39 €
WG.03.0069	RAL 7016 - antracite	W_CZU.C2.6.N_A.02.EU01	5902479664248	
WG.03.0071	RAL 8017 - brown	W_CZU.C2.6.N_A.03.EU01	5902479664255	
WG.03.0068	RAL 8003 - golden oak	W_CZU.C2.6.N_A.04.EU01	5902479664262	



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off 4 LEDs indicating: communication, power, manual mode, contact status

EU-MW-1	WG.05.0114	W_MW1.01.EU01.1	5902479661346
EU-MW-1-230V	WG.05.0116	W_MW1.02.EU02.1	5902479662374

101 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1	WG.05.0197	W_MWN1.01.EU01.1	5902479664507
EU-MWN-1 230V	WG.05.0117	W_MWN1.02.EU02.1	5902479664392

101 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140	W_MOD.RP4.6_A.01.EU01	5902479662824
------------	-----------------------	---------------

101 €



STT-868 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. **Available thread M28x1,5 adapter**

WG.12.0005	W_868.01.EU01.1	5902479661124
------------	-----------------	---------------

73 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016	W_869.01.EU01.1	5902479662381
------------	-----------------	---------------

88 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Fuctions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030	W_I1M.01.EU01.1	5902479661612
------------	-----------------	---------------

123 €



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm	P_002.02.00044.03.01	5902479661209	18 €
250cm	P_002.02.00045.03.01	5902479664279	19 €



EU-291P NTC WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for EU-L-9 controller

WG.03.0064	W_291P.02.EU01.1	5902479662732
------------	------------------	---------------

18 €



STT-230/2 THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5	T_000.00.000.00020	5902479660691	29 €
M28 x 1,5	T_000.00.000.00021	5902479661490	29 €



STT-230/2 S THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Nut with M30 x 1,5 screw thread, Stroke: 3,7 mm., Class: IP50. Opening time: 3 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5	T_000.00.000.00019	5902479661155	20 €
-----------	--------------------	---------------	------



STT-230/2 T THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5	T_000.00.203.00020	5902479663630	20 €
-----------	--------------------	---------------	------



STT-230/2 M THERMOELECTRIC ACTUATOR ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42.. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

NEW !	M30 x 1,5	T_000.00.000.00073	5902479665108	20 €
--------------	-----------	--------------------	---------------	------

WIRED FLOOR HEATING SYSTEM - 10 SERIES

EU-L-10 WIRED CONTROLLER FOR THERMOSTATIC ACTUATORS (10 SECTIONS)

- Functions:**
- possibility of control up to 50 thermostatic actuators by 18 outputs:
 - 8 zones have 2 outputs each (in case of greater amount of actuators max load is 0,3 A),
 - 2 zones have 1 output each (in case of greater amount of actuators max load is 0,3 A),
 - one 230V output for pump
 - voltage-free contact (e.g. for controlling the heating device)
 - voltage contact for controlling floor pump
 - 2 minutes delay for switching on voltage-free contact and pump contact



WG.20.004	W_L10.01.EU01.1	5902479662497	151 €
-----------	-----------------	---------------	--------------

ROOM REGULATORS AND SENSORS POWERED FROM MAIN CONTROLLER - DEDICATED

EU-R-10b DEDICATED WIRED ROOM REGULATOR FOR EU-L-10 CONTROLLER

Functions: room temperature control, wired communication **3-wire / no batteries**

Equipment: built-in room temperature sensor, LCD display, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0180	W_R10B.01.EU01.1	5902479662503	41 €
WG.11.0181	W_R10B.01.EU02.1	5902479662343	

EU-R-10s PLUS DEDICATED WIRED ROOM REGULATOR FOR EU-L-10 CONTROLLER

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight, **3-wire / no batteries**

Equipment: built-in room temperature sensor, LCD display,



WG.11.0184	W_POK.297.6.D_R10SP.01.EU01	5902479663876	65 €
WG.11.0185	W_POK.297.6.D_R10SP.02.EU01	5902479664187	

ROOM REGULATORS AND TEMPERATURE SENSORS - BATTERY, WIRED

EU-294 v1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.



WG.11.0144	W_294V1.01.EU01.1	5902479661018	37 €
WG.11.0147	W_294V1.01.EU02.1	5902479662053	

EU-T-2.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,



NEW!

WG.11.0642	W_POK.294.2.6.P_PB.01.PL01	5902479665085	57 €
------------	----------------------------	---------------	-------------

EU-295 v3 TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries



WG.11.0151	W_295V3.01.EU01.1	5902479661544	50 €
------------	-------------------	---------------	-------------

EU-297 v3 TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, Flush mountable in electrical box (ø60mm)



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0155	W_POK.297.6.P_PB.01.EU01	5902479662947	80 €
WG.11.0156	W_POK.297.6.P_PBN.01.EU01	5902479662954	

EU-297z v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0158	W_POK.297.6.PZ_PZ.01.EU01	5902479663746	88 €
WG.11.0604	W_POK.297.6.PZ_PZN.01.EU01	5902479663753	

EU-T-3.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,



* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0160	W_POK.297.6.P_PB.02.EU01	5902479663906	77 €
WG.11.0601	W_POK.297.6.P_PBN.02.EU01	5902479664217	

EU-T-4.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,



* White or black casing. In case of lack of colour selection color will be chosen randomly.

	W_POK.290.6.V3_N.01.EU01	5902479664590	55 €
--	--------------------------	---------------	-------------



EU-292 v3 WIRED TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, heating/cooling function, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0137

W_292V3.01.EU01.1

5902479660257

WG.11.0139

W_292V3.01.EU02.1

5902479660264

73 €



EU-293 v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function, wired communication, Flush mountable in electrical box (ø60mm)

Equipment: built-in room temperature sensor, front panel made of 1mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0142

W_POK.292.6.P_PB.01.EU01

5902479662886

WG.11.0143

W_POK.292.6.P_PBN.01.EU01

5902479662893

92 €



EU-293z v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.064

W_POK.292N.6.P_293N.PZ.EU01

5902479663791

W_POK.292N.6.P_293N.PZ.EU02

5902479663807

109 €



EU-F-2z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,

Equipment: built-in room temperature sensor, LCD display with no backlight, power supply: 230V,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0609

W_POK.F2.6_F2Z.01.EU01

5902479664095

WG.11.0636

W_POK.F2.6_F2Z.02.EU01

5902479664132

66 €



EU-F-4z v1 WIRED ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass, 230V powered,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0633

W_POK.F4.6_A.01.EU01

5902479664118

W_POK.F4.6_A.03.EU01

5902479664156

92 €

ACCESORIES AND ACTUATORS



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm

P_002.02.00044.03.01

5902479661209

250cm

P_002.02.00045.03.01

5902479664279

18 €

19 €



STT-230/2 THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 or M28x1,5 screw thread, Stroke: 3,5 mm, Class: IP40. Opening time: under 5 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.000.00020

5902479660691

M28 x 1,5

T_000.00.000.00021

5902479661490

29 €

29 €



STT-230/2 S THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Nut with M30 x 1,5 screw thread, Stroke: 3,7 mm., Class: IP50. Opening time: 3 min. Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.000.00019

5902479661155

20 €



STT-230/2 T THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP45. Opening time: under 3,5 min. Stroke - 3,7mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

M30 x 1,5

T_000.00.203.00020

5902479663630

20 €



STT-230/2 M THERMOELECTRIC ACTUATOR

ACTUATOR IS NORMALLY CLOSED (NC).

Technical Data: Fittings: nut with M30 x 1,5 screw thread, Class - IP42. Opening time: under 4 min. to 3mm, Stroke - 5mm,Max. operation temperature: 60°C. Power supply: 230V 50Hz

NEW !

M30 x 1,5

T_000.00.000.00073

5902479665108

20 €

INTERNET ROOM REGULATOR for heating device

EU-WiFi 8S p WIFI MODULE FOR THERMOELECTRIC ACTUATORS (FLUSH-MOUNTABLE)



Functions: Control of up to 8 heating zones using:

- possibility of connecting up to 8 **EU-C-8r, EU-C-mini, EU-CL-mini** wireless sensors or wireless room regulators **EU-R-8b, EU-R-8bw, EU-R-8b PLUS, EU-R-8s, EU-R-8s PLUS, EU-R-8z, EU-F-8z**
- relay output NO/NC (to control the heating device, when heat needed)
- possibility of connecting up to 6 pcs of wireless electric actuators STT-868 or STT-869 for each zone
- 1 wireless temperature sensor EU-C-mini included

Maintain of the system via web app: www.emodul.eu

WG.20.0059

W_STR.8S.6.ME_W8S.01.EU01_K

5902479664194

217 €



EU-C-mini WIRELESS ROOM TEMPERATURE SENSOR

Dimensions: 37mm x 37mm x 16mm

WG.03.0085

W_CMINI.01.EU01.1

5902479661636

33 €



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off LEDs indicating: communication, power, manual mode, contact status

EU-MW-1
EU-MW-1-230V

WG.05.0114

WG.05.0116

W_MW1.01.EU01.1

W_MW1.02.EU02.1

5902479661346

5902479662374

101 €

WIRED ROOM REGULATORS two-state (ON/OFF)



EU-294 v1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlit

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0144

WG.11.0147

W_294V1.01.EU01.1

W_294V1.01.EU02.1

5902479661018

5902479662053

37 €



EU-T-2.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries,

NEW!

WG.11.0642

W_POK.294.2.6.P_PB.01.PL01

5902479665085

57 €



EU-295 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0151

W_295V3.01.EU01.1

5902479661544

50 €



EU-297 v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0155

WG.11.0156

W_POK.297.6.P_PB.01.EU01

W_POK.297.6.P_PBN.01.EU01

5902479662947

5902479662954

80 €



EU-297z v3 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0158

WG.11.0604

W_POK.297.6.PZ_PZ.01.EU01

W_POK.297.6.PZ_PZN.01.EU01

5902479663746

5902479663753

88 €



EU-T-3.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0160

WG.11.0601

W_POK.297.6.P_PB.02.EU01

W_POK.297.6.P_PBN.02.EU01

5902479663906

5902479664217

77 €



EU-T-4.1 WIRED TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly t, manual mode, day/night program, temporary display backlit, Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

W_POK.290.6.V3_N.01.EU01

5902479664590

55 €



TECH
CONTROLLERS



EU-292 v3 WIRED TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication

Equipment: built-in room temperature sensor, front panel made of 3mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0137

W_292V3.01.EU01.1

5902479660257

WG.11.0139

W_292V3.01.EU02.1

5902479660264

73 €



EU-293 v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function, wired communication, Flush mountable in electrical box (ø60mm)

Equipment: built-in room temperature sensor, front panel made of 1mm glass

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0142

W_POK.292.6.P_PB.01.EU01

5902479662886

WG.11.0143

W_POK.292.6.P_PBN.01.EU01

5902479662893

92 €



EU-293z v3 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication, possibility of powering regulator from EU-L-5s controller

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.064

W_POK.292N.6.P_293N.PZ.EU01

5902479663791

W_POK.292N.6.P_293N.PZ.EU02

5902479663807

109 €

WIRELESS ROOM REGULATORS two-state (ON/OFF)



EU-294 v2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, heating/cooling program with time limit,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, no backlight

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0148

W_294V2.01.EU01.1

5902479661117

WG.11.0149

W_294V2.01.EU02.1

5902479662138

71 €



EU-T-2.2 WIRELESS TWO-STATE ROOM REGULATOR WITH HUMIDITY SENSOR

Functions: room temperature control, humidity sensor, heating/cooling program with time limit, wireless communication

Equipment: built-in room temperature and humidity sensor, LCD display, 2xAAA Batteries, no backlight, set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0595

W_POK.2942.6.R_RBN.01.EU01

5902479664040

WG.11.0596

W_POK.2942.6.R_RBN.02.EU01

5902479664057

76 €



EU-292 v2 WIRELESS TWO-STATE ROOM REGULATOR (3MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function

Equipment: built-in room temperature sensor, front panel made of 3mm glass, controller stand, set for wireless communication, possibility of external sensor readout (optional)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0135

W_292V2.01.EU01.1

5902479660233

WG.11.0136

W_292V2.01.EU02.1

5902479660240

129 €



EU-293 v2 WIRELESS TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, temperature control on the basis of floor temperature (in case of using floor sensor), Optimum Start function, heating/cooling function, wireless communication, Flush mountable in electrical box (ø60mm)

Equipment: built-in room temperature sensor, front panel made of 1mm glass, set for wireless communication,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0140

W_POK.292.6.P_PB.01.EU01

5902479662886

WG.11.0141

W_POK.292.6.P_PBN.01.EU01

5902479662893

157 €



EU-293z v2 WIRED TWO-STATE ROOM REGULATOR (1MM GLASS)

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wireless communication,

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm), set for wireless communication,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0646

W_POK.292N.6.R_293N.RZ.EU01

5902479663814

W_POK.292N.6.R_293N.RZ.EU02

5902479663821

177 €



EU-295 v2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, wireless communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight,

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries

WG.11.0150

W_295V2.01.EU01.1

5902479661537

97 €



EU-297 v2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wireless communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight.

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, set for wireless communication, Flush mountable in electrical box (ø60mm)

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0154

W_POK.297.6.R_RB.01.EU01

5902479662923

142 €

WG.11.0599

W_POK.297.6.R_RBN.01.EU01

5902479662930



EU-297z v2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight.

Equipment: built-in room temperature sensor, LCD display, 230V powered, Flush mountable in electrical box (ø60mm), set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0157

W_POK.297.6.R_RZ.01.EU01

5902479663760

151 €

WG.11.0602

W_POK.297.6.RZ_RZN.01.EU01

5902479663777



EU-T-3.2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, day/night program, heating/cooling function, wired communication, additional control based on floor temperature (if floor sensor is used), temporary display backlight.

Equipment: built-in room temperature sensor, LCD display, 2xAAA Batteries, set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0159

W_POK.297.6.R_RB.02.EU01

5902479663890

140 €

WG.11.0643

W_POK.297.6.R_RBN.02.EU01

5902479664200



EU-T-4.2 WIRELESS TWO-STATE ROOM REGULATOR

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, Optimum Start function, heating/cooling function, wireless communication

Equipment: built-in room temperature sensor, LCD display, 2xAA Batteries, set for wireless communication

* White or black casing. In case of lack of colour selection color will be chosen randomly.

W_POK.290.6.V2_N.01.EU01

5902479664613

110 €

WIRED ROOM REGULATORS WITH RS COMMUNICATION



EU-280 WIRED ROOM REGULATOR WITH RS COMMUNICATION

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port
Room regulator can operate only with TECH controllers equipped with RS communication: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

WG.11.0109

W_280.01.EU02.01

5902479660325

223 €



EU-281 WIRED ROOM REGULATOR WITH RS COMMUNICATION (2MM GLASS)

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port
Room regulator can operate only with TECH controllers equipped with RS communication: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0116

W_281.01.EU01.1

5902479660332

225 €

WG.11.0120

W_281.01.EU02.1

5902479662039

WIRELESS ROOM REGULATORS WITH RS COMMUNICATION



EU-280 + EU-260 WIRELESS ROOM REGULATOR WITH RS COMMUNICATION

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port, set for wireless communication

Room regulator can operate only with TECH controllers equipped with RS communication: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

WG.11.0110

W_280_260_EU01

5902479660875

262 €



EU-281 C WIRELESS ROOM REGULATOR WITH RS COMMUNICATION (2MM GLASS, FLUSH-MOUNTABLE)

Functions: control of the room temperature, control of the central heating boiler temperature, control of the DHW temperature, control of the mixing valves temperature, outside temperature monitoring, weekly-based heating mode, alarm, parental lock, displaying current room and CH boiler temperatures, alarm history, software update via USB, Easy installation in a flush mounting box (ø60mm).

Equipment: large, clear, colour touch 4,3"-LCD display, built-in room temperature sensor, power supply 12V DC RS communication cable for the boiler controller, USB port, set for wireless operation, easy installation in an electrical box (ø60mm). Power supply: 230V 50Hz.

Room regulator can operate only with TECH controllers equipped with RS comon: EU-37RS, EU-48, EU-480, EU-880zPID, EU-i-3, EU-i-2, EU-i-1, EU-i-1m, EU-i-1CWU,

* White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0118

W_281C.01.EU01.1

5902479661162

291 €

WG.11.0119

W_281C.01.EU02.1

5902479662145

ROOM REGULATORS FOR 55mm FRAME SYSTEMS



EU-F-2z v1 WIRED ROOM REGULATOR FOR 55mm FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,
Equipment: built-in room temperature sensor, LCD display with no backlight, power supply: 230V,
 * White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0609	W_POK.F2.6_F2Z.01.EU01	5902479664095	66 €
WG.11.0636	W_POK.F2.6_F2Z.02.EU01	5902479664132	



EU-F-2z v2 WIRELESS ROOM REGULATOR FOR 55mm FRAME SYSTEMS

Functions: control of the room temperature, heating/cooling, display autolock function,
Equipment: built-in room temperature sensor, LCD display with no backlight, power supply: 230V, set for wireless communication,
 * White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0654	W_POK.F2.6.R_F2Z.02.EU01	5902479664101	122 €
WG.11.0657	W_POK.F2.6.R_F2Z.04.EU01	5902479664149	



F-4z v1 WIRED ROOM REGULATOR FOR 55mm FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wired communication
Equipment: built-in room temperature sensor, front panel made of 3mm glass, 230V powered,
 * White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0633	W_POK.F4.6_A.01.EU01	5902479664118	92 €
	W_POK.F4.6_A.03.EU01	5902479664156	



F-4z v2 WIRELESS ROOM REGULATOR FOR 55MM FRAME SYSTEMS

Functions: room temperature control, weekly heating program, manual mode, day/night program, temporary display backlight, additional control based on floor temperature (if floor sensor is used), Optimum Start function, heating/cooling function, wireless communication
Equipment: built-in room temperature sensor, front panel made of 3mm glass, power supply: 230V, set for wireless communication,
 * White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0628	W_POK.F4.6.R_A.02.EU01	5902479664125	157 €
	W_POK.F4.6.R_A.04.EU01	5902479664163	

REGULATORS FOR GAS BOILERS



EU-2801 WiFi ROOM REGULATOR WITH OPENTHERM COMMUNICATION + WIFI COMMUNICATION

Functions: smart maintaining the room set temperature, smart control of the CH boiler set temperature, changing the room set temperature basing on the outside temperature (weather-based control), outside temperature view, weekly-based heating program for room and boiler, displaying alarms from heating device, acces to temperature charts of heating device, alarm clock, parental lock, **WiFi communication**, **Maintain of the system via web app: www.emodul.eu**

Equipment: large, clear, colour-touchscreen, built-in room sensor, flush-mountable
 * White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0114	W_2801WIFI.01.EU01.1	5902479661377	362 €
WG.11.0115	W_2801WIFI.01.EU02.1	5902479662183	



EU-WiFi OT ROOM REGULATOR WITH OPENTHERM COMMUNICATION + WIFI COMMUNICATION

Functions: smart maintaining the room set temperature, smart control of the CH boiler set temperature, changing the room set temperature basing on the outside temperature (weather-based control), outside temperature view, weekly-based heating program for room and boiler, displaying alarms from heating device, acces to temperature charts of heating device, alarm clock, **WiFi communication**, **Maintain of the system via web app: www.emodul.eu**

Equipment: large screen, built-in room sensor, in set additional wireless temperature sensor **EU-R-8b** and wired outdoor temperature sensor **EU-291p NTC**
 * White or black casing. In case of lack of colour selection color will be chosen randomly.

WG.11.0108	W_POK.2811.6.OT_A.01.EU01	5902479662909	357 €
------------	---------------------------	---------------	-------

AIR CLEANING AND STERILIZING



OTS-15 OZONE GENERATOR 15g/h - ADJUSTABLE

Function: Ozone generator is designed for ozonation of all types of rooms, flats, cars and cargo spaces or air conditioning systems. The device is also intended for home use, office space and a range of other places such as a beauty salon or a dentist's office where disinfection of rooms is required. The ozone generator may also be used to disinfect and deodorise rooms. It is important to remember that during ozonation, people or animals are not allowed to stay in the room. **Programmable device operation time - the operation time can be adjusted to the size of the room (specifying the room dimensions), or set manually,**

Technical data: maximum performance: **up to 15 000 mg/h**, Method of ozone production: corona discharge, Fan capacity: 165 (±10%) m³/h, power consumption: 110W
 fuse: 1.6A, ambient operating temperature: 5-50°C, acceptable relative ambient humidity: <80% REL.H, weight: 2.7 kg, cable length: 1.5 m

WG.13.0032	W_INN.OZ1.6_A.01.EU01	5902479663708	
------------	-----------------------	---------------	--



OTS-30 OZONE GENERATOR 30g/h - ADJUSTABLE

Function: Ozone generator is designed for ozonation of all types of rooms, flats, cars and cargo spaces or air conditioning systems. The device is also intended for home use, office space and a range of other places such as a beauty salon or a dentist's office where disinfection of rooms is required. The ozone generator may also be used to disinfect and deodorise rooms. It is important to remember that during ozonation, people or animals are not allowed to stay in the room. **Programmable device operation time - the operation time can be adjusted to the size of the room (specifying the room dimensions), or set manually,**

Technical data: maximum performance: **up to 30 000 mg/h**, Method of ozone production: corona discharge, Fan capacity: 230 (±10%) m³/h, power consumption: 220W
 fuse: 1.6A, ambient operating temperature: 5-50°C, acceptable relative ambient humidity: <80% REL.H, weight: 3.2 kg, cable length: 1.5 m

WG.13.0033	W_INN.OZ1.6_B.01.EU01	5902479663715	
------------	-----------------------	---------------	--



SPT-31 INOX AIR STERILISER - ADJUSTABLE

Function: The main task of SPT-31 INOX is to eliminate bacteria, viruses, mould, fungi and other substances which are harmful to the body. The device uses UV radiation in order to effectively disinfect the air in a room. Thanks to the use of appropriate technology and wavelength, it is possible to conduct air sterilization on an ongoing basis without the need to leave the room. For this purpose, the device has been equipped with specialized lamps without the wavelength range of 100-230 nm, thanks to which they do not emit ozone. The air steriliser can be successfully used in offices, beauty salons, shops or homes.

Technical data: maximum power: 75W, standby power: 1.7W, **lamp power: 15W (in lamp 2x15W)**, type of lamp: Philips TUV T8 15W G15, lifespan: 9000 hours, **radiation: UV-C 253,7 nm wavelength**, **maximum air flow capacity: up to 260 m³/h**, maximum noise level: 44dB, device dimension: 145x295x625mm, filter dimensions: 255x135x10mm

WG.13.0004	W_INN.SPT.6_30.02.EU01	5902479664620	
	W_INN.SPT.6_30.03.EU01	5902479664637	

INSTALLATION CONTROLLERS



EU-27i INSTALLATION CONTROLLER (2 PUMPS)

Functions: CH pump control, control of additional DHW or floor pump, anti-stop function, anti-freeze function
Equipment: LCD display, CH temperature sensor, additional pump temperature sensor.

WG.14.0058

W_27i.01.EU01.1

5901445470319

78 €



EU-427i INSTALLATION CONTROLLER (3 PUMPS)

Functions: time-based or temperature-based control of the three pumps, anti-stop function, anti-freeze function, the possibility of setting any pump priorities, possibility of connecting a room regulator with traditional communication (a two-state regulator – ON/OFF)
Equipment: LCD display, three temperature sensors

WG.14.0065

W_427i.01.EU01.1

5901445470364

110 €



EU-513 INPUTS INTEGRATOR - 5

Functions: Integration of 5 voltage inputs, control of one 230V output

WG.05.0027

W_513.01.EU01.1

5902479661414

57 €



EU-517 2 HEATING CIRCUITS MODULE

Functions: control of two pumps, cooperation with two room regulators with traditional communication (on/off), control of potential free contact

WG.05.0158

W_517.01.EU01.1

5902479661230

57 €



EU-i-1m MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR) (EXPANSION MODULE FOR MAIN CONTROLLER)

Functions: control of the three- or four-way mixing valve, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication.

WG.05.0030

W_i1m.01.EU01.1

5902479661612

123 €



EU-i-1 MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR)

Functions: control of the three- or four-way mixing valve, valve pump control, the possibility of controlling two valves by means of additional i-1 or i-1m modules, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication, the possibility of connecting EU-505 Ethernet/EI-WiFi RS module. USB port for software update [Maintenance via emodul app](#)

Equipment: LCD display, mixing valve temperature sensor, return water temperature sensor, tank temperature sensor, external sensor.

WG.14.0067

W_i1.01.EU01.1

5902479661698

174 €



EU-i-1 DHW MIXING VALVE CONTROLLER (1 MIXING VALVE ACTUATOR + DHW)

Functions: control of the three- or four-way mixing valve, valve pump control, DHW pump control, the possibility of controlling two valves by means of additional i-1 or i-1m modules, return water temperature protection, weather-based regulation, week-based regulation, the possibility of connecting room regulator with RS or traditional communication, the possibility of connecting EU-505 Ethernet/EI-WiFi RS module. USB port for software update [Maintenance via emodul app](#)

Equipment: LCD display, mixing valve temperature sensor, return water temperature sensor, DHW temperature sensor, external sensor.

WG.14.0068

W_i1CWU.01.EU01.1

5902479661674

177 €



EU-i-2 PLUS INSTALLATION CONTROLLER WITH OPENTHERM (2 MIXING VALVE ACTUATORS)

Functions: Possibility of control heating device with OpenTherm, smooth control of the two mixing valves, two mixing valve pumps, DHW pump control, two configurable voltage-free outputs, two configurable voltage outputs, return water temperature protection. Weather-based and week-based regulation. Possibility of connecting three room regulators with standard communication (two-state, on/off). Possibility of connecting room regulator with RS communication (overview and eidtion of temperatures from main controller). The possibility of controlling two valves by means of additional i-1, i-1m, modules. the possibility of connecting EU-505 Ethernet/EI-WiFi RS modules, 2 outputs 0-10 V. [Maintenance via emodul app](#)

Equipment: colour LCD 4,3" touchscreen, 6 temperature sensors for any configuration, external sensor,

NEW!

WG.14.0164

W_INT.I3.6.2PJ_I2.01.EU01

5902479665061

332 €



EU-i-3 PLUS INSTALLATION CONTROLLER WITH OPENTHERM (3 MIXING VALVE ACTUATORS + SOLAR INSTALLATION)

Functions: Possibility of control heating device with OpenTherm, smooth control of the three mixing valves, three mixing valve pumps, DHW pump control, two configurable voltage-free outputs, two configurable voltage outputs, maintenance simply solar installation ,return water temperature protection. Weather-based and week-based regulation. Possibility of connecting three room regulators with standard communication (two-state, on/off). Possibility of connecting room regulator with RS communication (overview and eidtion of temperatures from main controller). The possibility of controlling two valves by means of additional i-1, i-1m modules. the possibility of connecting EU-505 Ethernet/EI-WiFi RS modules, 2 outputs 0-10 V, PWM signal. [Maintenance via emodul app](#)

Equipment: colour LCD 4,3" touchscreen, 6 temperature sensors for any configuration, external sensor, collector sensor (PT-1000)

WG.14.0072

W_INT.I3.6.3PJ_A.01.EU01

5902479661803

420 €



TECH
CONTROLLERS



EU-RI-1 WIRED ROOM REGULATOR WITH RS COMMUNICATION EU-I-2 OR EU-I-3 PLUS

Functions: room temperature control, day/night program, RS communication, temporary display backlight, work with installation controller EU-I-2, EU-I-3 (with new firmware) and EU-I-3 PLUS
Equipment: built-in room temperature sensor, LCD display.

WG.11.0216

W_POK.RI1.6_A.01.EU01

5902479663678

64 €



EU-11 DHW CIRCULATION REGULATOR

Functions: controlling circulating pump operation, monitoring the pre-set temperature in a heating circuit, smart control of the circulation system, protection against overheating (DHW pump activation), anti-stop function, adjustable pump operation time

Principle of operation: DHW circulation regulator is intended for controlling DHW circulation to suit individual user's needs. In an economical and convenient way, it reduces the time needed for hot water to reach the fixtures. It controls the circulating pump which, when the user draws water, accelerates the flow of hot water to the fixture, exchanging the water there for hot water at the desired temperature in the circulation branch and at the tap. The system monitors the temperature set by the user in the circulation branch and it activates the pump only when the pre-set temperature drops. Thus it does not generate any heat loss in the DHW system. It saves energy, water and equipment in the system (e.g. circulation pump).

WG.14.0043

W_11.01.EU01.1

5902479661704

211 €

SOLAR INSTALLATION CONTROLLERS



EU-401N PWM SOLAR INSTALLATION CONTROLLER

Functions: control of the solar pump using PWM signal, supervision and handling of the solar system operation, protection against overheating and freezing of the collector, voltage-free output, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules.

Equipment: large, clear LCD display, collector temperature sensor, heat accumulator temperature sensor.

WG.19.0013

W_401NPWM.01.EU01.1

5902479662411

150 €



EU-402N PWM SOLAR INSTALLATION CONTROLLER

Functions: control of the solar pump using PWM signal, control of the pumps (or the pump and the valve), the possibility of connecting additional device: circulation pump, electric heater or sending a signal to the CH boiler to fire it up, supervision and handling of the solar system operation using 17 possible configurations of the system, protection against overheating and freezing of the collector, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules.

Equipment: large, clear LCD display, two collector temperature sensors, two heat accumulator temperature sensors

WG.19.0015

W_402NPWM.01.EU01.1

5901445470562

174 €

PUMP CONTROLLERS



EU-19 PUMP CONTROLLER

Functions: CH pump control, anti-stop function.

Equipment: CH temperature sensor, potentiometer to adjust the set temperature

WG.14.0044

W_19.01.EU01.1

5901445470005

34 €



EU-20 PUMP CONTROLLER

Functions: CH pump control

Equipment: CH temperature sensor, potentiometer to adjust the set temperature

WG.14.0045

W_20.01.EU01.1

5901445470012

33 €



EU-21 PUMP CONTROLLER

Functions: CH pump control, possible operation as a thermostat, anti-stop function, anti-freeze function.

Equipment: CH temperature sensor, LED display

WG.14.0048

W_21.01.EU01.1

5901445470142

45 €



EU-21 R PUMP CONTROLLER

Functions: CH pump control, possible operation as a thermostat, anti-stop function, anti-freeze function, voltage-free contact

Equipment: CH temperature sensor, LED display

WG.14.0170

W_21R.01.EU01.1

5901445470753

52 €



EU-21 DHW PUMP CONTROLLER

Functions: DHW pump control, anti-stop function, anti-freeze function, potential-free output control, delta of DHW and CH temperatures to set, protection against DHW tank freezing

Equipment: 2x temperature sensor, LED display

WG.14.0048

W_21CWU.01.EU01.1

5901445470654

52 €



EU-21 BUFFER PUMP CONTROLLER

Functions: buffer pump control, anti-stop function, anti-freeze function, potential-free output control, protection against buffer tank freezing

Equipment: 2x temperature sensor, LED display

WG.14.0047

W_21BUFOR.01.EU01.1

5901445470661

52 €

CHARGING BOILER CONTROLLERS



EU-22 SIGMA CHARGING BOILER CONTROLLERS

Functions: control of the fan and CH pump, in SIGMA version (slower fan operation when the central heating approaches the set temperature)

Equipment: CH temperature sensor, LED display, temperature protection, additional stand for easy installation on the boiler.

WG.21.0060

W_22SIGMA.01.EU01.1

5901445470920

92 €



EU-24 SIGMA CHARGING BOILER CONTROLLERS

Functions: control of the fan and CH pump-, in SIGMA version (slower fan operation when the central heating approaches the set temperature)

Equipment: CH temperature sensor, LED display, temperature protection.

WG.21.0063

W_24SIGMA.01.EU01.1

5901445470937

98 €



EU-28 SIGMA CHARGING BOILER CONTROLLERS

Functions: control of the fan, CH pump, DHW pump control, the possibility of connecting two-state room regulator (on/off), in SIGMA version (slower fan operation when the central heating approaches the set temperature)

Equipment: CH temperature sensor, DHW temperature sensor, LCD display, temperature protection

WG.21.0067	W_28SIGMA.01.EU01.1	5901445470951	121 €
------------	---------------------	---------------	-------



EU-28 zPID CHARGING BOILER CONTROLLER

Functions: automatic control of the fan operation, CH and DHW pumps control, zPID software (smart settings for operating parameters)

Equipment: LCD display, CH temperature sensor, DHW temperature sensor, flue gas sensor, temperature protection.

WG.21.0070	W_28ZPID.01.EU01.1	5901445470289	179 €
------------	--------------------	---------------	-------



EU-81 CHARGING BOILER CONTROLLER

Functions: control of the fan, CH pump, DHW pump control, the possibility of connecting two-state room regulator (on/off)

Equipment: CH temperature sensor, DHW temperature sensor, LCD display, controller in metal casing for installation on the boiler

WG.21.0076	W_81.01.EU01.1	5901445470265	142 €
------------	----------------	---------------	-------



EU-81 zPID CHARGING BOILER CONTROLLER

Functions: automatic control of the fan operation, CH and DHW pumps control, zPID software (smart settings for operating parameters)

Equipment: LCD display, CH temperature sensor, DHW temperature sensor, flue gas sensor, temperature protection

WG.21.0085	W_81ZPID.01.EU01.1	5901445470302	201 €
------------	--------------------	---------------	-------



EU-880 zPID CHARGING BOILER CONTROLLER

Functions: automatic control of the fan operation, CH, DHW and additional pumps control, mixing valve control, possibility of connecting room regulator with RS communication (preview and edition of boiler parameters) or two-state room regulator (on/off), possibility of connecting and EU-505/EU-WiFi RS Ethernet module. Possibility of controlling two additional mixing valves using EU-i1m, EU-i-1 modules, zPID software (smart settings for operating parameters).

Equipment: large graphic display facilitating the controller operation, knob of impulse generator, CH, DHW, mixing valve, return water, and flue gas sensors, external wireless sensor, power supply cable for controller and pumps, temperature protection, single-module panel casing for installation on the boiler, controller in metal casing obudowie nakotłowej

WG.21.0092	W_880ZPID.01.EU01.1	5902479660004	357 €
------------	---------------------	---------------	-------

BOILER WITH FEEDER CONTROLLERS



EU-37n RS BOILER WITH FEEDER CONTROLLER

Functions: control of the fan and feeding screw or piston feeder (EU-37n RS H), CH and DHW pumps control, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules (*RS option), the possibility of controlling two valves by means of additional EU-i1m, EU-i-1 modules, the possibility of connecting room regulator with RS or traditional communication, weekly control (optional).

Equipment: LCD display, CH and DHW temperature sensor, feeder temperature sensor (protection), temperature protection, panel casing for installation on the boiler

version EU-37n RS H	WG.17.0061	W_37NRS.01.EU01.1	5902479661834	229 €
	WG.17.0064	W_37NRSH.01.EU01.1	5902479661841	



EU-480 N BOILER WITH FEEDER CONTROLLER

Functions: control of the fan and feeding screw or piston feeder (EU-480 H), CH, DHW, floor and circulation pumps control, control of the mixing valve, the possibility of connecting room regulator with RS or traditional communication, the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules, the possibility of controlling two valves by means of additional EU-i1m modules

Equipment: large graphic display facilitating the controller operation, knob of impulse generator, CH, DHW, mixing valve, return water, and flue gas sensors, external wireless sensor, power supply cable for controller and pumps, temperature protection, single-module panel casing for installation on the boiler, controller in metal casing

version EU-480 H	WG.17.0423	W_480N.01.EU01.1	5902479662565	447 €
	WG.17.0071	W_480H.01.EU01.1	5902479661179	

FIREPLACE CONTROLLERS



EU-391 zPID FIREPLACE CONTROLLER (COLOUR SCREEN, TOUCH BUTTONS)

Functions: control of the circulation pump, control of the additional pump, DHW pump or floor pump, buffer pump control or laddomat control, throttle control, a contactor switching the gas boiler on and of, depending on the desired circuit water temperature minus hysteresis, zPID software, buffer maintenance (two sensors), the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules. **Maintenance via emodul app**

Equipment: flue gas sensor, floor, DHW, CH, top and bottom buffer sensors, throttle 100mm (for an extra charge 120 or 150mm), colour screen

ø100	WG.21.0071	W_391ZPID.01.EU01.1_100	5902479660646	291 €
ø120	WG.21.0072	W_391ZPID.01.EU01.1_120	5902479662589	301 €
ø150		W_391ZPID.01.EU01.1_150	5902479662596	314 €



EU-392 zPID FIREPLACE CONTROLLER (COLOUR, TOUCHSCREEN)

Functions: control of the circulation pump, control of the additional pump, DHW pump or floor pump, buffer pump control or laddomat control, throttle control, a contactor switching the gas boiler on and of, depending on the desired circuit water temperature minus hysteresis, zPID software, buffer maintenance (two sensors), the possibility of connecting EU-505 Ethernet/EU-WiFi RS modules. **Maintenance via emodul app**

Equipment: flue gas sensor, floor, DHW, CH, top and bottom buffer sensors, throttle 100mm (for an extra charge 120 or 150mm), colour touchscreen

ø100	WG.21.0073	W_392ZPID.01.EU01.1_100	5902479660639	345 €
ø120	WG.21.0074	W_392ZPID.01.EU01.1_120	5902479662602	356 €
ø150	WG.21.0075	W_392ZPID.01.EU01.1_150	5902479662619	368 €



THROTTLE

Available diameters: 100mm, 120mm, 150mm

ø100	W_PRZE.01.EU01.1_100	5902479661247	
ø120	W_PRZE.01.EU01.1_120	5902479662473	
ø150	W_PRZE.01.EU01.1_150	5902479662480	



ADDITIONAL MODULES / ACCESSORIES



EU-MW-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MW-1) or voltage relay (EU-MW-1-230V), operation in manual mode, wireless communication with main controller or temperature sensor (master/slave mode), in case of loss of communication, the contact is switched off. LEDs indicating: communication, power, manual mode, contact status

EU-MWN-1
EU-MWN-1-230V

WG.05.0114
WG.05.0116

W_MW1.01.EU01.1
W_MW1.02.EU02.1

5902479661346
5902479662374

101 €



EU-MWN-1 EXECUTIVE MODULE

Main assets: voltage-free relay (EU-MWN-1) or voltage relay (EU-MWN-1-230V), wireless communication with main controller (slave mode), in case of loss of communication, the contact is switched off

EU-MWN-1
EU-MWN-1-230V

WG.05.0197
WG.05.0117

W_MWN1.01.EU01.1
W_MWN1.02.EU02.1

5902479664507
5902479664392

101 €



EU-RP-4 SIGNAL REPEATER

The signal repeater is a small electronic device that increases the range of wireless communication between devices without the need for additional cables. Thanks to the device, controller which are away from main unit will be able to establish a stable connection

WG.05.0140

W_MOD.RP4.6_A.01.EU01

5902479662824

101 €



EU-67 PELLETS LEVEL SENSOR

EU-67 sensor is intended for measuring the level of solid biofuels (pellet, oat, maize, etc.) not only in central heating boilers' tanks but also in grain silos, where the max. spacing between measuring sensors is not greater than 3,5m. To have a successful measurement it is necessary to deliver only dry fuel. Main principle of operation of the device is based on setting the level of biofuel using properly installed capacitive sensors.

WG.03.0102

W_67.01.EU01.1

5901445470425

294 €



EU-505 INTERNET MODULE

Functions: remote control of the floor heating system, control of the set temperature in each zone, possibility of define the schedules, preview the temperatures history for each zone, possibility of personalization the main screen, alarms notifications via e-mail.

Equipment: power supply: 5V DC, T-connector for RS, RS communication cable for main controller.

WG.05.0025

W_505.01.EU01.1

5902479660578

201 €



EU-WiFi RS WIFI INTERNET MODULE (WIFI CONNECTION)

Functions: Same as in EU-505. Internet connection via WiFi signal

WG.05.0040

W_WIFIRS.01.EU01.1

5902479660974

215 €



STZ-120 T MIXING VALVE ACTUATOR

Functions: The actuator with 3-point signal control in 230V AC (50 Hz). manual mode, It comes with 1,5m cable, rotation time: 120 sec, adapters in set for: ESBE, Afriso, Herz, Womix, Honeywell, Wita.

W_SIL.Z01.6_A.01.EU01

5902479663739

119 €



STT-868 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1.5V batteries. **Available thread M28x1,5 adapter**

WG.12.0005

W_868.01.EU01.1

5902479661124

73 €



STT-869 WIRELESS ELECTRIC ACTUATOR

The device is compatible with: EU-WiFi 8S, EU-WiFi 8S mini, EU-16S WiFi, EU-L-8e, EU-L-9r and EU-L-4 controller.

Technical data: Output – nut with M30x1,5 thread; Communication – wireless, frequency 868MHz; power supply: 2xAAA 1,5V batteries. new design, registration button built on the front of actuator, **Available thread M28x1,5 adapter**

WG.12.0016

W_869.01.EU01.1

5902479662381

88 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

DANFOSS RAN > M30x1,5 >

T_000.00.000.00014

5902479661872

10 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

DANFOSS RTD-N > M30x1,5 >

T_000.00.000.00015

5902479661889

10 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

VALVEX > M30x1,5 >

WG.12.0003

W_045.00.000.00001

5902479662756

10 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

PINTOSI > M26x1,5 >

WG.12.0002

W_045.00.000.00002

5902479662763

10 €



THREAD ADAPTER FOR Wireless electric actuator STT-868 or STT-869

COMAP/HERZ > M30x1,5 >

WG.12.0001

W_045.00.000.00003

5902479662770

10 €



EU-260 SET FOR WIRELESS RS COMMUNICATION

Set for a wireless RS communication used in addition to room regulator consists of two modules:
V1 module is dedicated to the controller with RS communication and own power supply.
V2 Module is dedicated to the controller with RS communication without own power supply (e.g. EU-280).
An example application may also be communication between EU-505 Ethernet with the main CH boiler controller.

WG.05.0023	W_260.01.EU01.01	5902479660158	73 €
------------	------------------	---------------	------



EU-262 SET FOR WIRELESS COMMUNICATION

Wireless communication set for two-state room regulators.

WG.05.0024	W_262.01.EU01.01	5902479660165	73 €
------------	------------------	---------------	------



RS splitter

WG.05.0147	W_ROZRS.01	5902479661506	13 €
------------	------------	---------------	------



RS splitter RS-8

8 RS outputs

W_ROZ.RS.EU01.1	5902479665078	30 €
-----------------	---------------	------



2-POLE CONTACTOR WITH PROTECTION

Appliance: Control one- or multipole electrical devices. Major application is to control heating systems, motors or pumps.
Rated current: 20 A, **Coil supply voltage:** 230 V AC (50 Hz), **Maximum coil current consumption:** 8 VA, **Maximum coil load:** up to 4kW (depending on the applied protection)
The set includes: contactor, fuse, wiring (power supply, male and female plugs)

W_MS2B.01.EU01.1	5902479661513	112 €
------------------	---------------	-------

ADDITIONAL SENSORS



EU-291P KTY WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for controllers equipped with mixing valve control
e.g. EU-430, i-1, i-1m, EU-880 zPID, EU-480

WG.03.0063	W_291P.01.EU01.1	5902479660899	18 €
------------	------------------	---------------	------



EU-291P NTC WIRED OUTSIDE TEMPERATURE SENSOR

Sensor dedicated for EU-L-9 controller

WG.03.0064	W_291P.02.EU01.1	5902479662732	18 €
------------	------------------	---------------	------



FLOOR TEMPERATURE SENSOR - NTC TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

150cm	P_002.02.00044.03.01	5902479661209	18 €
250cm	P_002.02.00045.03.01	5902479664279	19 €



SEMICONDUCTOR TEMPERATURE SENSOR - KTY TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

Resistance at 25°C: 2kΩ
Coefficient: 0.79 %/K
Accuracy : 1%
Range of operation: -25-90°C

150cm	P_002.01.00014.03.01	5902479660905	18 €
150cm with plug	P_002.01.00014.03.02	5902479664286	19 €
250cm	P_002.01.00019.03.01	5902479664293	19 €
250cm with plug	P_002.01.00019.03.02	5902479664309	20 €



SEMICONDUCTOR TEMPERATURE CLIP-ON SENSOR - KTY TYPE

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

Resistance at 25°C: 2kΩ
Coefficient: 0.79 %/K
Accuracy : 1%
Range of operation: -25-90°C

150cm	P_002.01.00033.03.01	5902479663685	18 €
250cm	P_002.01.00035.03.01	5902479664316	19 €



BIMETALLIC SENSOR – (THERMAL OVERLOAD RELAY)

(plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO

Activation temperature 85°C
Accuracy: +/- 3°C
Application: temperature protection

P_002.09.00131.03.01	5902479660912	18 €
----------------------	---------------	------

	SEMICONDUCTING TEMPERATURE SENSOR FOR SOLAR SYSTEM- PT1000 TYPE (silicone cable insulation) 1,5m Resistance at 0°C: 1kΩ Accuracy : +/-0.3°C Range of operation: -25+180°C	P_002.03.00066.03.01	5902479661391		30 €
	SEMICONDUCTING TEMPERATURE SENSOR FOR WATER TANK- PT1000 TYPE (FOR SOLAR SYSTEMS) cable length 1,5m Resistance at 0°C: 1kΩ Accuracy : +/-0.3°C Range of operation: -25+95°C	P_002.03.00059.03.02	5902479660929		20 €
	FLUE GAS TEMPERATURE SENSOR - PT1000 TYPE (cable insulation made of glass fiber) Resistance at 0°C: 1kΩ Accuracy : +/-0.3°C Range of operation: -25+480°C	P_002.03.00071.03.02	5902479660936		56 €
30 cm 30cm with plug		P_002.03.00071.03.03	5902479664323		57 €
	PHOTOCELL – FIRE SENSOR (plastified PVC cable insulation) 0,25m Application: pellet-fired boilers	P_002.05.00089.03.01	5902479660943		20 €
	HALL GENERATOR (HALL'S SENSOR) (plastified PVC cable insulation) 1,5m - extra charge for each meter: 1 EUR NETTO Application: boilers with piston feeder	P_002.06.00103.03.01	5902479660950		20 €
250cm					
	REED RELAY (plastified PVC cable insulation) 2,5m - extra charge for each meter: 1 EUR NETTO Application: boilers with piston feeder	P_002.06.00113.03.01	5902479660967		20 €
	SAFETY THERMOSTAT – (STB) Activation temperature: 90+110°C Accuracy : +/-3+5°C Maximum current: 16A Application: temperature protection	S_030.00.046.00002	5902479661216		20 €
	ANTENNA EXTENSION - SMA SMA antenna cable for extending the antenna used in the L-8 controller Cable length 5m. Cable type - coaxial, wave impedance - 50Ω Cable / passage construction: SMA socket, SMA plug	T_000.00.000.00008	5902479661520		17 €
FANS					
	STW-70 HMSK BLOWING FAN FOR CENTRAL HEATING BOILERS 25-50 KW (Power consumption – 70W) old RV-12	T_000.00.000.00001	5902479660752		
	STW-60 EMSK BLOWING FAN FOR CENTRAL HEATING BOILERS UP TO 35 KW (Power consumption – 60W) old RV-14	T_000.00.000.00002	5902479660769		
	WPA-117 BLOWING FAN FOR CENTRAL HEATING BOILERS (Power consumption - 34 W)	T_000.00.000.00003	5901445470494		
	WPA-120 BLOWING FAN FOR CENTRAL HEATING BOILERS (Power consumption - 83W / 75W)	T_000.00.000.00004	5902479661605		
	WPA-140 BLOWING FAN FOR CENTRAL HEATING BOILERS (Power consumption - 100W)	T_000.00.000.00005	5901445470500		



TECH
CONTROLLERS

ul. Biała Droga 31, 34-122 Wieprz
tel. +48 33 330 00 07 | fax. +48 33 845 45 47
poczta@techsterowniki.pl | www.controllers.com